

A3 Colour MFP

MX-2651

Office MFP with enhanced security that keeps pace with changing workforce needs



- Print, Copy, Scan, Fax, File
- Paper capacity: Std 650 Max 6,300 sheets
- Print Release function gives users the ability to send and store documents on a main MFP for authentication and print out from any networked MFP
- Shorter warm up time helps reduce energy consumption and improve productivity
- Pages per minute: 26 B/W 26 Colour
- Customisable, tiltable 10.1 inch colour LCD touchscreen with easy UI mode enables intuitive navigation of MFP functions
- Optional single sign-on brings easy access to public cloud storage services
- Multi layered security features

Specifications

GENERAL

| | |
|--|-----------------------|
| Engine speed Colour ppm (A4) | 26 |
| Engine speed B/W ppm (A4) | 26 |
| Engine speed Colour ppm (A3) | 15 |
| Engine speed B/W ppm (A3) | 15 |
| Paper size: Min.-Max. | A5 - SRA3 |
| Paper weight (g/m2) | 60 - 300 |
| Paper capacity:Std (sheets) | 650 |
| Paper capacity: Max. (sheets) | 6300 |
| Warm Up Time (sec.) | 20 |
| Memory general min/max (GB) | 5 |
| Harddisk | STD |
| Harddisk capacity (GB) | 500 |
| Duplex | STD |
| Power requirements - rated local AC voltage (Hz) | 200 - 240V, 50 / 60Hz |
| Power consumption (kW) | 1.84 |
| Dimensions (mm) | 608 x 650 x 834 |
| Weight (kg) | 79 |

DOCUMENT FEEDER

| | |
|----------------------------|-----|
| Original capacity (sheets) | 100 |
|----------------------------|-----|

DOCUMENT FILING

| | |
|---|---|
| Document filing (Standard / Option) | STD |
| Document filing capacity- main and custom folders (pages) | 20000 |
| Document filing capacity- quick file folder (pages) | 10000 |
| Stored jobs | Copy, print, scan, fax transmission |
| Storage folders | Quick file folder, main folder, custom folder (max. 1000) |
| Confidential storage | . |

FAX

| | |
|--|---|
| Fax (Standard / Option) | OPT |
| Compression method | MH / MR / MMR / JBIG |
| Communication protocol | Super G3 / G3 |
| Transmission time (sec) | 2 |
| Modem Speed (bps) | 33600 - 2400 |
| Transmission resolution | STD 203.2 x 97.8 dpi / Ultra Fine 406.4 x 391 dpi |
| Document Size (Min) | A5 |
| Document Size (Max) | A3 |
| Memory (MB) | 1024 |
| Grey Scale levels | 256 |
| Dial Registration; rapid/speed dial | 2000 |
| Broadcast Transmission (max. destinations) | 500 |

WIRELESS LAN

| | |
|----------------------------------|---|
| Wireless LAN (Standard / Option) | OPT |
| Compliant regulation | IEEE802.11n / g / b |
| Access mode | Infrastructure mode, Software AP mode |
| Security | WEP, WPA / WPA2-mixed PSK, WPA / WPA2-mixed EAP, WPA2 PSK, WPA2 EAP |

COPIER

| | |
|--|---------------------------------|
| Original paper size (Max.) | A3 |
| First copy out time Colour (sec.) | 6.7 |
| First copy out time B/W (sec.) | 4.7 |
| E-sort Std | . |
| Continuous copy (Max. copies) | 9,999 |
| Resolution Scan B/W (dpi) | 600 x 600, 600 x 400, 600 x 300 |
| Resolution Scan Colour (dpi) | 600 x 600 |
| Resolution Print (dpi) | 600 x 600, 9600 x 600 |
| Gradation (equivalent levels) - Colour | 256 |
| Zoom range (%) | 25 - 400 |
| Preset copy ratios | 10 |

SCANNER

| | |
|-------------------------------------|---|
| Network Scanner (Standard / Option) | STD |
| Scan method Push scan and Pull scan | . |
| Resolution push scan (dpi) | 100, 150, 200, 300, 400, 600 |
| Resolution pull scan (dpi) | 75, 100, 150, 200, 300, 400, 600, 50 to 9600 |
| File formats | TIFF, PDF, PDF / A, encrypted PDF, compact PDF, JPEG, XPS |
| Scan destinations Desktop | . |
| Scan destination FTP, Email | . |
| Scan destination Network folder | . |
| Scan destination USB memory | . |

PRINTER

| | |
|-------------------------------------|--|
| Resolution (dpi) | 600 x 600, 9600 x 600 |
| Network Printer (Standard / Option) | STD |
| Interface Std/Opt | USB 2.0,10Base-T / 100Base-TX / 1000Base-T |
| Supported OS Standard | Windows Server 2008 / 2008R2 / 2012 / 2012R2 / 2016, Windows Vista, Windows 7, 8.1, 10 |
| Supported OS Options | Mac OS X 10.4, 10.5, 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13 |
| Network protocols | TCP / IP (IPv4 and IPv6) |
| Printing protocols | LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, FTP for downloading print files, IPP |
| PDL Std/Opt | STD PCL 6 emulation; OPT Adobe® PostScript® 3™ |
| Available fonts | 80 (PCL), 139 (Adobe PostScript 3) |

FINISHING

| | |
|-------------------------------|------------|
| Output Capacity Max. | 500 - 3000 |
| Staple Capacity (sheets) Max. | 65 |
| Saddle Stitch | OPT |
| Off-set shifting | STD |
| Hole punch | OPT |

TONER YIELD

| | |
|--------------------------------|-------|
| Black (pages at 5% coverage) | 40000 |
| Cyan (pages at 5% coverage) | 24000 |
| Magenta (pages at 5% coverage) | 24000 |
| Yellow (pages at 5% coverage) | 24000 |