## MX-4071

## Office MFP with enhanced security features and superior functionality for flexible working



- Print, Copy, Scan, Fax, File
- Paper capacity: Std 650 Max 6,300 sheets
- Print Release function gives users the ability to send and store documents on a main MFP for authentication and print out from any networked MFP
- Short warm up time and motion sensor ensure that the device is always ready for immediate operation
- Pages per minute: 40 B/W 40 Colour
- Customisable, tiltable 10.1 inch colour LCD touchscreen with easy UI mode enables intuitive navigation of MFP functions
- Single sign-on brings easy access to public cloud storage services
- OCR allows users to convert scanned documents into editable MS Office files (pptx, xlsx, docx) and searchable PDFs



<sup>\*</sup>¹ Can be used from any of five network-connected MFPs. \*² This function is enabled via Qualcomm® DirectOfficeTM technology. \*³ MX-4071/MX-3571/MX-3071 only. \*⁴ Images per minute; when feeding A4 sheets. ¹¹ ABC

## Specifications

Engine speed Colour ppm (A4) 40 Engine speed B/W ppm (A4) 40 Engine speed Colour ppm (A3) 20 Engine speed B/W ppm (A3) 20 Paper size: Min.-Max. A5 - SRA3 Paper weight (g/m2) 60 - 300 Paper capacity:Std (sheets) 650 Paper capacity: Max. (sheets) 6300 Warm Up Time (sec.) 20 Memory general min/max (GB) Harddisk STD Harddisk capacity (GB) 500 Duplex STD 200 - 240V, 50 / 60Hz

Power requirements - rated local AC voltage

(Hz)

Power consumption (kW) 1.84

Dimensions (mm) 616 x 660 x 838

Weight (kg) 88

**DOCUMENT FEEDER** 

Original capacity (sheets) 150

**DOCUMENT FILING** 

Document filing (Standard / Option) STD Document filing capacity- main and custom 20000 folders (pages) 10000

Document filing capacity- quick file folder

(pages)

Stored jobs Copy, print, direct print, scan, fax

transmission

Storage folders Quick file folder, main folder, custom folder (max. 1000)

**Confidential storage** 

Fax (Standard / Option) OPT

Compression method MH / MR / MMR / JBIG

**Communication protocol** Super G3 / G3

Transmission time (sec)

Modem Speed (bps) 33600 - 2400

Transmission resolution STD 203.2 x 97.8 dpi / Ultra Fine 406.4 x 391 dpi

Document Size (Min) Α5 Document Size (Max) A3

Memory (MB) 1024 **Grey Scale levels** 256 Dial Registration; rapid/speed dial 2000 **Broadcast Transmission (max. destinations)** 500

**WIRELESS LAN** 

Wireless LAN (Standard / Option) STD

**Compliant regulation**  $\mathsf{IEEE802.11n}\,/\,\mathsf{g}\,/\,\mathsf{b}$ 

Access mode Infrastructure mode, Software AP

mode

Security WEP, WPA / WPA2-mixed PSK, WPA

/ WPA2-mixed EAP, WPA2 PSK,

WPA2 EAP

Original paper size (Max.) А3 First copy out time Colour (sec.) 6.7 First copy out time B/W (sec.) 4.7 E-sort Std Continuous copy (Max. copies) 9,999

Resolution Scan B/W (dpi)

600 x 600, 600 x 400 Resolution Scan Colour (dpi) 600 x 600

Resolution Print (dpi) 1200 x 1200, 600 x 600, 9600 x 600

Gradation (equivalent levels) - Colour 256 Zoom range (%) 25 - 400 Preset copy ratios 10

Network Scanner (Standard / Option) STD Scan method Push scan and Pull scan

Resolution push scan (dpi) 100, 150, 200, 300, 400, 600 Resolution pull scan (dpi) 75, 100, 150, 200, 300, 400, 600, 50

to 9600 File formats

TIFF, PDF, PDF / A-1a, PDF / A-1b, encrypted PDF, compact PDF, JPEG, XPS, searchable PDF, Microsoft Office (pptx, xlsx, docx),

text (TXT), rich text (RTF)

Scan destinations Desktop Scan destination FTP, Email Scan destination Network folder

PRINTER

Scan destination USB memory

Resolution (dpi) 1200 x 1200, 600 x 600, 9600 x 600 Network Printer (Standard / Option)

Interface Std/Opt USB 2.0,10Base-T / 100Base-TX /

1000Base-T, Optional secondary LAN support

Supported OS Standard Windows Server 2008 / 2008R2 /

2012 / 2012R2 / 2016, Windows 7, 8.1, 10, Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13

**Network protocols** TCP / IP (IPv4 and IPv6)

**Printing protocols** LPR, Raw TCP (port 9100), POP3 (email printing), HTTP, FTP for

downloading print files, IPP, SMB,

PDL Std/Opt STD PCL 6 emulation, Adobe®

PostScript® 3™

Available fonts 80 (PCL), 139 (Adobe PostScript 3)

**FINISHING** 

**Output Capacity Max.** 500 - 3000 Staple Capacity (sheets) Max. Saddle Stitch OPT Off-set shifting STD Hole punch OPT

**TONER YIELD** 

Black (pages at 5% coverage) 40000 Cyan (pages at 5% coverage) 24000 Magenta (pages at 5% coverage) 24000 Yellow (pages at 5% coverage) 24000

Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Local Inc., QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. PCL is a registered in the US and other countries. PCL is a registered trademark of Hewlet-Packard Company, Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm incorporated, registered in the US and other countries. DirectOffice is a trademark of Selevities. Qualcomm incorporated in the US and other countries. DirectOffice is a product name and logory of the product names and logory of the pro

